



# OTANI<sup>®</sup>

**DRIVING CONFIDENCE**

## **AGRICULTURAL RADIAL TIRE CATALOG 2022**



[WWW.OTANITIRE.COM](http://WWW.OTANITIRE.COM)





# AGRICULTURAL RADIAL

RIM DIAMETER	TIRE SIZE	LI/SS	PATTERN	TYPE	RIM WIDTH		SECTION WIDTH	OVERALL DIAMETER	RC	SLR	SRI	INFLATION PRESSURE	LOAD CAPACITY PER TIRE (Kg)			
					REC. RIM	ALT. RIM							SPEED (km/h)			
					(inch)	(inch)							10	30	40	50
24"	320/85R24 (12.4R24)	122 A8 119 B	A-10	TT/TL	W11	W9, W10	322	1134	3465	515	550	9 / 0.6	1110	885	825	715
												12 / 0.8	1290	1030	960	840
												15 / 1.0	1470	1175	1095	980
												17 / 1.2	1650	1320	1230	1105
												20 / 1.4	1830	1460	1365	1230
	23 / 1.6	2010	1605	<b>1500</b>	1360											
	340/85R24 (13.6R24)	125 A8 122 B	A-10	TT/TL	W12	W11	346	1181	3555	542	575	9 / 0.6	1220	975	910	790
												12 / 0.8	1420	1135	1060	930
												15 / 1.0	1620	1295	1205	1080
												17 / 1.2	1820	1455	1355	1200
												20 / 1.4	2020	1615	1505	1360
	23 / 1.6	2215	1770	<b>1650</b>	1500											
	380/85R24 (14.9R24)	131 A8 128 B	A-10	TT/TL	W12	W11, W13	380	1256	3750	560	600	9 / 0.6	1440	1150	1075	1020
												12 / 0.8	1675	1340	1250	1160
												15 / 1.0	1910	1530	1425	1320
17 / 1.2												2145	1715	1600	1500	
20 / 1.4												2380	1905	1775	1650	
23 / 1.6	2615	2090	<b>1950</b>	1800												
30"	420/85R30 (16.9R30)	140 A8 137 B	A-10	TT/TL	W15L	W13, W14L	438	1465	4455	660	700	9 / 0.6	1845	1475	1375	1215
												12 / 0.8	2145	1715	1600	1440
												15 / 1.0	2450	1955	1825	1640
												17 / 1.2	2750	2195	2050	1830
												20 / 1.4	3050	2435	2275	2070
	23 / 1.6	3350	2675	<b>2500</b>	2300											
	460/85R30 (18.4R30)	145 A8 142 B	A-10	TT/TL	W16L	W14L, W15L	471	1529	4686	694	725	9 / 0.6	2140	1710	1595	1440
												12 / 0.8	2490	1990	1860	1550
												15 / 1.0	2840	2270	2120	1900
												17 / 1.2	3190	2550	2380	2100
20 / 1.4												3540	2830	2640	2400	
23 / 1.6	3890	3150	<b>2900</b>	2650												
34"	460/85R34 (18.4R34)	147 A8 144 B	A-10	TT/TL	W16L	W14L, W15L	466	1666	4965	721	775	9 / 0.6	2270	1815	1695	1490
												12 / 0.8	2640	2110	1970	1785
												15 / 1.0	3015	2410	2245	2040
												17 / 1.2	3385	2705	2525	2285
												20 / 1.4	3755	3000	2800	2540
23 / 1.6	4125	3295	<b>3075</b>	2800												
38"	460/85R38 (18.4R38)	149 A8 146 B	A-10	TL	W16L	W14L, W15L	457	1753	5270	805	825	9 / 0.6	2400	1915	1790	1640
												12 / 0.8	2790	2230	2080	1880
												15 / 1.0	3180	2545	2375	2120
												17 / 1.2	3575	2855	2665	2450
												20 / 1.4	3965	3170	2960	2710
23 / 1.6	4355	3480	<b>3250</b>	3000												

\* REC. RIM : RECOMMENDED RIM \*ALT. RIM : ALTERNATIVE RIM \*RC : ROLLING CIRCUMFERENCE \*SLR : STATIC LOAD RADIUS \*SRI : SPEED RADIUS INDEX \*MOST COMMON SPEED = 40km/h