

OTANI[®]
DRIVING CONFIDENCE

AGRICULTURAL TIRE

CATALOG 2025





1964

Otani Group founded by Dr.Kiattichai Limpichotipong. He started tire business by open the small tire shop in Ubon Ratchathani in the Northeast of Thailand.

1974

Dr.Kiattichai Limpichotipong moved to his hometown, Nakhon Pathom and opened the retread tire company's name "PARATIRE".

2007

Incorporated Otani Radial Co., Ltd. to manufacture radial tires for truck and bus.

1986

Founded "Otani Tire Co., Ltd." to manufacture bias ply tires.

2017

In September 2017 Otani Radial started commercial run of PCR production.

OTANI GROUP PROFILES

Name : Otani Tire Company Limited
 Products : Agricultural Tires
 Off the Road Tires
 Bias Truck and Bus Tires
 Incorporation : 1986
 Paid-up capital : THB 500 Million
 Address : 55 Mu 7 Phetkasem Road KM.37, Klongmai,
 Sam Phran, Nakhon Pathom 73110 Thailand

Name : Otani Radial Company Limited
 Products : Passenger Car Radial Tires
 Truck and Bus Radial Tires
 Incorporation : 2007
 Paid-up capital : THB 3,000 Million
 Address : 96 Mu 3 Rimklongbanrai Road, Bangkaew,
 Nakhon Chai Sri, Nakhon Pathom 73120 Thailand



BIAS TIRE



K-81

K-82


T-22

T-25

F-30

F-32

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)
14"	6-14	4	F-33	R1/G1	TT	5AJ	30	28	195	300	162	655	28
	7-14	4	F-33	R1/G1	TT	5AJ	30	25	170	355	178	687	28
	6.50-14	6	F-33	R1	TT	4.50E	30	46	315	710	183	699	19
15"	4.00-15	6	T-22	II	TT	3.00D	30	64	440	425	114	610	10
	11L-15SL	10	K-81	II/F3	TL	8LB	30	44	305	1060	256	830	12
16"	6.00-16	6	T-22	II	TT	4.00E	30	48	330	560	177	740	15
		8	T-22	II	TT	4.00E	30	65	450	670	180	750	15
	7-16	4	F-33	R1/G1	TT	5AJ	30	24	165	387	183	740	26
		8	F-30	-	TT	5.50F	40	40	275	875	207	893	57
	7.50-16	4	F-33	R1	TT	5.50F	40	35	240	750	216	814	20
		8	F-33	R1	TT	5.50F	40	54	370	875	220	816	20
		8	F-34	R1	TT	5.50F	40	54	370	875	208	814	25
		6	T-22	II	TT	5.50F	40	44	305	670	210	814	20
	8-16	8	T-22	II	TT	5.50F	40	54	370	875	210	814	20
		8	T-25	II	TT	5.50F	40	54	370	875	208	805	17
		4	F-33	R1/G1	TT	W6	30	18	125	487	211	796	31
		6	F-33	R1/G1	TT/TL	W6	30	28	195	615	211	798	31
	9.5-16	6	F-33	R1/G1	TT	W8	30	32	220	730	245	850	30
		6	F-80	R2	TT	W8	30	32	220	730	260	845	43
	9.00-16	8	F-33	R1	TT	W8	40	45	310	1090	234	843	20
		10	T-22	II	TT	W8	40	52	360	1500	232	848	17
10.00-16	8	T-22	II	TL	W8	40	41	285	1215	272	898	19	
11.00-16	8	T-22	II	TL	W10	40	36	250	1320	305	947	22	
11L-16SL	12	K-81	II/F3	TL	8LB	30	52	360	1250	263	832	12	
18"	7.50-18	8	F-33	R1	TT	5.50F	40	54	370	950	210	860	20
		8	T-22	II	TT	5.50F	40	54	370	950	220	864	20
	8-18	4	F-33	R1/G1	TT	W6	30	18	120	515	221	840	31
		6	F-33	R1/G1	TT/TL	W6	30	28	195	670	222	840	31
		6	F-35	R1/G1	TT	W6	30	42	195	670	222	845	34
		8	F-35	R1/G1	TT	W6	30	95	290	850	222	845	34
13.0/65-18	16	K-82	II/F3	TL	11.00	40	95	655	2800	330	898	12	
20"	8.3-20	6	F-35	R1	TT	W7	30	35	240	710	208	890	30
	9.5-20	6	F-36	R1	TT	W7	40	32	220	850	240	945	43
		8	F-36	R1	TT	W7	40	41	285	975	244	948	43
11.2-20	8	F-35	R1	TT	W9	40	36	250	1150	280	1010	30	
22"	9.5-22	6	F-36	R1	TT	W8	40	31	215	900	240	1010	40
24"	8.3-24	6	F-35	R1	TT	W7	40	34	235	800	208	996	30
		6	F-35	R1	TT	W8	40	30	205	850	241	1048	30
	9.5-24	6	F-37	R1	TT	W8	40	30	205	850	241	1085	57
		4	F-37	R1	TT	W10	40	18	125	750	282	1098	57
	11.2-24	6	F-37	R1	TT	W10	40	26	180	1060	284	1103	57
		8	F-39	R1	TT	W10	40	35	240	1250	284	1110	42
	12.4-24	8	F-33	R1	TT	W11	40	32	220	1285	286	1160	28
		10	F-33	R1	TT	W11	40	36	250	1550	288	1160	28
		12	F-33	R1	TT	W11	40	48	330	1600	288	1161	28
		4	F-37	R1	TT	W11	40	16	110	850	318	1160	57
6		F-37	R2	TT/TL	W11	40	25	170	1215	320	1165	57	
8		F-37	R2	TT	W11	40	32	220	1285	322	1170	57	



BIAS TIRE



F-33

F-34

F-35

F-36

F-37

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)
24"	13.6-24	6	F-37	R2	TT	W12	40	22	150	1215	345	1210	57
		8	F-37	R2	TT	W12	40	28	195	1400	348	1215	57
		8	F-39	R1	TT	W12	40	28	195	1400	346	1212	42
		12	F-39	R1	TT	W12	40	36	250	1650	348	1215	42
	14.9-24	8	F-32	R1	TT/TL	W13	40	26	180	1800	389	1240	30
		12	F-32	R1	TT/TL	W13	40	38	260	2180	395	1245	30
		6	F-33	R1	TT/TL	W13	40	20	140	1550	378	1280	35
		8	F-33	R1	TT	W13	40	26	180	1800	385	1285	35
		12	F-33	R1	TT/TL	W13	40	38	260	2180	386	1286	35
		8	F-37	R1	TT	W13	40	26	180	1800	378	1285	60
		8	G-45	R4	TT/TL	DW13	40	30	205	2300	397	1271	27
		10	G-45	R4	TT/TL	DW13	40	36	250	2800	405	1272	27
	15.5/80-24	12	F-39	R1	TL	W12	40	58	400	4875	390	1275	38
	16.9-24	8	G-45	R4	TT/TL	DW15L	40	28	195	2650	440	1360	27
		10	G-45	R4	TT/TL	DW15L	40	32	220	2900	445	1362	27
		12	G-45	R4	TT/TL	DW15L	40	38	160	3250	450	1363	27
	17.5L-24	10	G-45	R4	TT/TL	DW15L	40	32	220	2800	456	1310	27
		12	G-45	R4	TT/TL	DW15L	40	36	250	2995	460	1321	27
	18.4-24	10	G-45	R4	TT/TL	DW16L	40	28	195	3350	472	1412	28
		12	G-45	R4	TT/TL	DW16L	40	36	250	3750	480	1414	28
19.5L-24	10	G-45	R4	TT/TL	DW16L	40	30	205	3000	495	1312	27	
	12	G-45	R4	TT/TL	DW16L	40	34	235	3450	496	1314	27	
	14	G-45	R4	TT/TL	DW16L	40	40	275	3750	498	1315	27	
21L-24	12	G-45	R4	TT/TL	DW16L	40	34	235	3447	558	1410	28	
25"	23.5-25	20	F-41	E2/L2	TL	19.5/2.5	10	55	380	10900	630	1638	54
26"	13.6-26	6	F-35	R1	TT/TL	W12	40	22	150	1250	345	1276	47
		8	F-35	R1	TT	W12	40	26	180	1600	348	1280	47
		6	F-37	R2	TT	W12	40	22	150	1250	345	1260	57
		8	F-37	R2	TT	W12	40	26	180	1600	345	1261	57
	23.1-26	16	F-38	R2	TT/TL	DW20B	40	32	220	4375	615	1605	42
28L-26	26	F-38	LS-2	TL	DW25B	10	32	220	4375	720	1660	55	
28"	12.4-28	6	F-37	R1	TT	W11	10	25	170	1285	315	1260	53
		8	F-33	R1	TT	W11	40	26	180	1500	305	1257	28
		10	F-33	R1	TT	W11	40	32	220	1650	306	1259	28
		12	F-33	R1	TT	W11	40	34	235	1750	307	1260	28
	13.6-28	6	F-37	R2	TT	W12	40	23	160	1450	345	1310	57
		8	F-37	R2	TT	W12	40	29	200	1650	348	1313	57
	14.9-28	6	F-35	R1	TT	W13	40	20	140	1650	372	1361	40
		8	F-35	R1	TT	W13	40	26	180	1900	375	1363	40
		12	F-35	R1	TT	W13	40	38	260	2300	378	1365	40
		6	F-36	R1	TT	W13	40	20	140	1650	378	1385	55
		8	F-36	R1	TT	W13	40	26	180	1900	380	1388	55
	16.9-28	8	F-33	R1	TT	W15L	40	25	170	2180	430	1430	40
		10	F-33	R1	TT	W15L	40	29	200	2430	435	1435	40
		12	F-80	R2	TT	W15L	40	35	240	2725	439	1435	57
		8	G-45	R4	TT/TL	DW15L	40	28	195	2800	429	1400	27
10		G-45	R4	TT/TL	DW15L	40	32	220	3075	430	1405	27	
12		G-45	R4	TT/TL	DW15L	40	38	260	3450	432	1410	27	

BIAS TIRE



F-38

F-39

F-41

F-80

F-85

G-45

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)
30"	14.9-30	8	F-35	R1	TT	W15L	30	26	180	1950	395	1436	48
		8	F-36	R2	TT	W15L	30	26	180	1950	384	1420	55
	16.9-30	8	F-33	R1	TT	W15L	40	25	170	2300	436	1483	40
		10	F-33	R1	TT	W15L	40	28	195	2430	437	1486	40
		12	F-33	R1	TT	W15L	40	34	235	2500	438	1490	40
		14	F-33	R1	TT	W15L	40	38	260	3000	439	1495	40
	18.4-30	10	F-39	R1	TT	W15L	40	28	195	2430	439	1486	53
		8	F-33	R1	TT	W16L	40	20	140	2430	480	1545	46
		10	F-33	R1	TT	W16L	40	26	180	2900	480	1545	46
		12	F-33	R1	TT	W16L	40	33	230	3250	483	1548	46
		8	F-39	R1	TT	W16L	40	20	140	2430	480	1544	53
		10	F-39	R1	TT	W16L	40	26	180	2900	483	1546	53
		12	F-39	R1	TT	W16L	40	33	230	3250	487	1548	53
		14	F-39	R1	TT	W16L	40	38	260	3450	488	1550	53
12		F-80	R2	TT	W16L	40	33	230	3250	491	1595	77	
32"		9.5-32	6	F-35	R1	TT	W8	40	30	210	1060	240	1255
	12.4-32	6	F-35	R1	TT	W12	40	33	230	1600	315	1265	40
34"	16.9-34	8	F-39	R1	TT	W15L	40	25	170	2430	463	1640	53
		10	F-39	R1	TT	W15L	40	29	200	2650	475	1644	53
	18.4-34	8	F-33	R1	TT	W16L	40	20	140	2650	480	1635	46
		10	F-33	R1	TT	W16L	40	26	180	3000	480	1637	46
		10	F-36	R2	TT	W16L	40	26	180	3000	468	1640	50
		10	F-39	R1	TT	W16L	40	26	180	3000	483	1659	53
	6	F-85	R2	TT	W16L	40	16	110	2000	491	1722	81	
38"	13.6-38	8	F-38	R1	TT	W12	40	29	200	1950	345	1555	40
		8	F-38	R1	TT	W14L	40	26	180	1850	401	1555	34
	15.5-38	10	F-38	R1	TT	W14L	40	32	220	2180	403	1560	34
		8	F-38	R1	TT	W15L	40	25	170	2575	430	1685	40
	16.9-38	10	F-38	R1	TT	W15L	40	29	200	2725	433	1690	40
		10	F-39	R1	TT	W16L	40	26	180	2900	487	1795	53
	18.4-38	8	F-85	R2	TT	W16L	40	20	140	2725	485	1798	81
		8	F-85	R2	TT	W18L	40	19	130	3150	535	1904	85



OTANI®

DRIVING CONFIDENCE

OTANI TIRE CO., LTD.

55 MU 7 PHETKASEM ROAD KM.37,
KLONGMAI, SAM PHRAN,
NAKHON PATHOM 73110 THAILAND

WEBSITE :

E-MAIL :

OFFICIAL LINE ACCOUNT :

FACEBOOK FANPAGE :

WWW.OTANITIRE.COM

SALES@OTANITIRE.COM

[@OTANITIRE](https://www.facebook.com/OTANITIRE)

OTANI TIRE