


OTANI[®]
DRIVING CONFIDENCE

TRUCK AND BUS BIAS TIRE

CATALOG 2025





BIAS TIRE



JUMBO-RIB K-706 K-707 K-90 L-88 M-RIB P-10 R-88 S-60

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	MAX LOAD DUAL	
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
13"	6.00-13	8	U-77	TT	94 L	4.50	670	1477	600	1325	60	415	171	650	10
	6.45-13	8	S-68	TL	78 L	4.00	425	937	-	-	28	195	153	605	11
14"	6.00-14	8	M-RIB	TT	98/96 L	4.50	750	1650	710	1570	60	415	181	687	11
		8	U-77	TT	98/96 L	4.50	750	1650	710	1570	60	415	182	683	10
		8	S-70	TT	98/96 L	4.50	750	1650	710	1570	60	415	175	675	12
		8	M-RIB	TT	102/100 L	4.50	850	1870	800	1760	62	425	187	705	11
	6.50-14	8	S-78	TT	102/100 L	4.50	850	1870	800	1760	62	425	179	703	10
		8	U-77	TT	102/100 L	4.50	850	1870	800	1760	62	425	188	702	10
		10	JUMBO-RIB	TT	105/103 L	4.50	925	2040	875	1930	75	515	187	705	10
		10	M-RIB	TT	105/103 L	4.50	925	2040	875	1930	75	515	187	705	11
14.5"	7-14.5	8	K-706	TL	102/98 L	6.00	850	1870	750	1650	70	485	189	691	7
	8-14.5	12	K-706	TL	117/112 L	6.00	1285	2830	1120	2470	100	690	209	718	8
15"	9-14.5	12	K-706	TL	122/118 L	7.00	1500	3305	1320	2910	100	690	226	721	8
	6.50-15	8	S-66	TT	103/101 L	4.50	875	1930	825	1820	60	415	195	710	12
		8	S-78	TT	105/103 L	5.50	925	2040	875	1930	60	415	200	766	12
		10	M-RIB	TT	113/108 L	5.50	1150	2540	1000	2200	75	515	198	766	12
		10	S-66	TT	113/108 L	5.50	1150	2540	1000	2200	75	515	204	762	13
		12	S-78	TT	113/108 L	5.50	1150	2540	1000	2200	75	515	208	768	12
		12	M-RIB	TT	117/112 L	5.50	1285	2830	1120	2470	90	620	210	768	12
	7.00-15	12	S-66	TT	117/112 L	5.50	1285	2830	1120	2470	90	620	208	768	13
		12	S-78	TT	117/112 L	5.50	1285	2830	1120	2470	90	620	210	769	12
		12	M-RIB	TT	120/118 L	6.00	1400	3080	1320	2910	87	600	210	784	12
		12	S-66	TT	120/118 L	6.00	1400	3080	1320	2910	87	600	220	780	14
		14	M-RIB	TT	122/121 K	6.00	1500	3300	1450	3200	95	655	210	785	12
		14	S-66	TT	122/121 K	6.00	1500	3300	1450	3200	95	655	210	785	14
	7.50-15	16	K-706	TT	133/128 G	6.50	2060	4540	1800	3960	130	895	234	845	13
	10.00-15	16	K-706	TT	141/136 G	7.50	2575	5680	2240	4940	115	795	282	915	13
16"	6.50-16	10	M-RIB	TT	107/103 L	4.50	975	2150	875	1930	75	515	186	754	11
		10	S-66	TT	107/103 L	4.50	975	2150	875	1930	75	515	195	758	10
		10	S-78	TT	107/103 L	4.50	975	2150	875	1930	75	515	180	754	12
		12	M-RIB	TT	111/109 L	4.50	1090	2400	1030	2270	83	570	188	768	11
		12	S-66	TT	111/109 L	4.50	1090	2400	1030	2270	83	570	198	768	10
		12	S-78	TT	111/109 L	4.50	1090	2400	1030	2270	83	570	186	757	12
	7.00-16	8	S-70	TT	109/107 L	5.50	1030	2270	975	2150	62	425	205	803	16
		10	M-RIB	TT	113/111 L	5.50	1150	2540	1090	2400	72	495	204	790	12
		10	S-66	TT	113/111 L	5.50	1130	2540	1090	2400	72	495	205	791	14
		12	M-RIB	TT	116/114 L	5.50	1250	2760	1180	2600	83	570	205	793	12
		12	S-66	TT	116/114 L	5.50	1250	2760	1180	2600	83	570	205	793	14
		12	S-70	TT	116/114 L	5.50	1250	2760	1180	2600	83	570	209	805	16
	7.50-16	8	S-70	TT	113/107 L	6.00	1150	2540	975	2150	60	415	228	805	17
		8	S-78	TT	113/107 L	6.00	1150	2540	975	2150	60	415	216	826	12
		8	S-79	TT	113/107 L	6.00	1150	2540	975	2150	60	415	216	826	11
		10	S-78	TT	116/112 L	6.00	1250	2760	1120	2470	80	550	224	826	12
		12	M-RIB	TT	121/119 L	6.00	1450	3200	1360	3000	87	600	224	825	12

BIAS TIRE



- S-63
- S-66
- S-67
- S-68
- S-70
- S-78
- S-79
- U-068
- U-77

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD	MAX LOAD		MAX LOAD		RELATIVE		TREAD	MAX LOAD		
						RIM WIDTH	SINGLE		DUAL		PRESSURE		DEPTH	DUAL		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION	OVERALL	
													WIDTH	DIAMETER		
16"	7.50-16	12	S-66	TT	121/119 L	6.00	1450	3200	1360	3000	87	600	217	823	14	
		12	S-70	TT	121/119 L	6.00	1450	3200	1360	3000	87	600	217	819	17	
		12	S-78	TT	121/119 L	6.00	1450	3200	1360	3000	87	600	217	827	12	
		14	M-RIB	TT	123/121 K	6.00	1550	3420	1450	3200	96	660	226	823	12	
		14	S-66	TT	123/121 K	6.00	1550	3420	1450	3200	96	660	218	827	14	
		14	S-70	TT	123/121 K	6.00	1550	3420	1450	3200	96	660	220	819	17	
	8.25-16	14	S-78	TT	123/121 K	6.00	1550	3420	1450	3200	96	660	218	828	12	
		16	U-068	TT	124/122 G	6.00	1600	3520	1500	3300	110	760	223	846	17	
		14	M-RIB	TT	126/125 K	6.50	1700	3740	1650	3640	83	570	233	845	12	
		14	S-66	TT	126/125 K	6.50	1700	3740	1650	3640	83	570	232	850	15	
		16	U-068	TT	129/128 K	6.50	1850	4080	1800	3960	105	725	228	848	18	
		18	U-068	TT	132/130 K	6.50	2000	4400	1900	4180	120	825	230	850	18	
20"	8.25-20	14	L-88	TT	136/132 G	6.50	2240	4940	2000	4400	115	795	230	977	14	
		14	U-77	TT	136/132 G	6.50	2240	4940	2000	4400	115	795	236	971	17	
	9.00-20	14	L-88	TT	141/137 G	7.00	2575	5680	2300	5080	110	760	260	1017	14	
		14	S-66	TT	141/137 G	7.00	2575	5680	2300	5080	110	760	260	1017	17	
			14	U-77	TT	141/137 G	7.00	2575	5680	2300	5080	110	760	260	1020	17
	10.00-20	14	K-707	TT	144/139 G	7.50	2800	6150	2430	5360	100	690	270	1058	10	
		16	K-90	TT	146/142 G	7.50	3000	6600	2650	5840	115	795	282	1065	18	
		16	L-88	TT	146/142 G	7.50	3000	6600	2650	5840	115	795	280	1058	14	
		16	S-66	TT	146/142 G	7.50	3000	6600	2650	5840	115	795	280	1067	17	
		16	S-67	TT	146/142 G	7.50	3000	6600	2650	5840	115	795	274	1076	21	
		16	U-77	TT	146/142 G	7.50	3000	6600	2650	5840	115	795	277	1061	17	
	11.00-20	18	S-63	TT	149/145 G	7.50	3250	7150	2900	6400	125	860	270	1076	30	
		18	S-67	TT	149/145 G	7.50	3250	7150	2900	6400	125	860	280	1067	21	
		16	L-88	TT	150/145 G	8.00	3350	7400	2900	6400	115	795	300	1087	14	
		16	P-10	TT	150/145 G	8.00	3350	7400	2900	6400	115	795	296	1094	18	
		16	U-77	TT	150/145 G	8.00	3350	7400	2900	6400	115	795	305	1093	17	
		18	P-10	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	298	1095	18	
		18	R-88	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	298	1120	30	
		18	S-60	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	290	1110	24	
		18	S-63	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	290	1110	30	
		18	S-67	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	293	1090	21	
	12.00-20	18	U-068	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	297	1090	18	
		18	U-77	TT	152/147 G	8.00	3550	7850	3075	6800	125	860	305	1093	17	
		18	L-88	TT	154/150 K	8.50	3750	8250	3350	7400	125	860	326	1120	14	
18		U-068	TT	154/150 K	8.50	3750	8250	3350	7400	125	860	318	1140	18		
14.00-20	18	U-77	TT	154/150 K	8.50	3750	8250	3350	7400	125	860	318	1135	19		
	18	S-79	TT	144F	8.50	2790	6170	-	-	100	690	400	1273	17		
22"	11.00-22	16	L-88	TT	150/145 G	8.00	3350	7400	2900	6400	115	795	298	1131	14	
		18	L-89	TT	155/150 G	8.00	3875	8550	3350	7400	125	860	300	1133	14	
		18	U-068	TT	155/150 G	8.00	3875	8550	3350	7400	125	860	300	1145	18	
24"	12.00-24	18	L-88	TT	158/154 F	8.50	4250	9350	3750	8250	115	795	324	1243	14	
		18	U-77	TT	158/154 F	8.50	4250	9350	3750	8250	115	795	314	1235	19	
		20	L-88	TT	160/155 F	8.50	4500	9900	3875	8550	130	895	328	1245	14	
		20	U-77	TT	160/155 F	8.50	4500	9900	3875	8550	130	895	317	1244	19	



OTANI®

DRIVING CONFIDENCE



OTANI TIRE CO., LTD.

55 MU 7 PHETKASEM ROAD KM.37,
KLONGMAI, SAM PHRAN,
NAKHON PATHOM 73110 THAILAND

WEBSITE :

E-MAIL :

OFFICIAL LINE ACCOUNT :

FACEBOOK FANPAGE :

WWW.OTANITIRE.COM

SALES@OTANITIRE.COM

[@OTANITIRE](https://www.facebook.com/OTANITIRE)

OTANI TIRE