












OTANI[®]
DRIVING CONFIDENCE

TRUCK AND BUS RADIAL TIRE

CATALOG 2025





	 ALL POSITION	 STEER	 DRIVE	 TRAILER
 LONG HAUL	OH-107 OH-154 OH-150 OH-155 OH-151 OH-152 OH-153	OH-119 WB	OH-319 OH-350	OH-109 OH-111 WB
 REGIONAL	OH-113 OH-117 OH-121 NEW OH-122 NEW ● OH-127 NEW ●	OH-120	OH-301 OH-311 OH-320 OH-322 OH-351	OH-102 WB OH-118 OH-108 WB OH-123 NEW ●
 ON-OFF	OH-201 OH-206 OH-202 OH-208 OH-203 OH-209 OH-204 OH-210 OH-205 OH-213 NEW		OH-303 OH-306 WB OH-307 OH-317 OH-312 OH-402 OH-312+	
 OFF-ROAD	OH-401 OH-403 OH-404		OH-320	
 HIGHWAY BUS	OH-107 BUS			
 CITY BUS	OH-501			
 WINTER	OH-650			

RADIAL TIRE



OH-102

OH-107

OH-107 BUS

OH-108

OH-109

OH-111

OH-113

OH-117

OH-118

OH-119

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
16"	6.50R16LT	12	OH-117	TL	111/109 L	5.50	1090	2405	1030	2270	95	650	TBA	TBA	TBA	
	7.00R16LT	12	OH-311	TL	117/116 L	5.50	1285	2810	1250	2700	90	620	16.0	204	783	
		12	OH-117	TL	117/116 L	5.50	1285	2810	1250	2700	90	620	11.0	201	774	
	7.50R16LT	14	OH-117	TL	118/114 L	5.50	1320	2910	1180	2600	112	770	11.0	201	774	
		14	OH-117	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	11.0	218	800	
		14	OH-201	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	210	809	
		14	OH-208	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	214	807	
		14	OH-314	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	212	807	
		16	OH-117	TL	124/120 L	6.00	1600	3520	1400	3085	116	800	11.0	217	800	
		18	OH-117	TL	129/128 L	6.00	1850	4080	1800	3970	123	850	11.0	218	800	
	8.25R16LT	18	OH-208	TL	129/128 K	6.00	1850	4080	1800	3970	123	850	13.5	214	807	
		18	OH-317	TL	129/128 G	6.00	1850	4080	1800	3970	123	850	16.0	216	809	
		16	OH-117	TL	132/130 L	6.50	2000	4410	1900	4190	116	800	12.5	239	856	
		16	OH-201	TL	132/130 L	6.50	2000	4410	1900	4190	116	800	13.5	235	858	
		16	OH-314	TL	132/130 L	6.50	2000	4410	1900	4190	116	800	13.5	230	858	
	205/85R16LT	12	OH-117	TL	117/115 L	5.50	1285	2835	1215	2680	87	600	10.0	200	756	
	ST235/80R16	14	OH-170	TL	129/125 M	6.50	1850	4080	1650	3640	110	760	9.0	232	775	
ST235/85R16	14	OH-170	TL	132/127 M	6.50	2000	4400	1750	3860	110	760	9.0	235	783		
17.5"	9.5R17.5	14	OH-117	TL	129/127 L	6.75	1850	4080	1750	3860	110	760	14.0	238	840	
		14	OH-311	TL	129/127 L	6.75	1850	4080	1750	3860	110	760	14.0	238	844	
		18	OH-117	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	14.0	238	840	
		18	OH-311	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	14.0	238	844	
	205/65R17.5	18	OH-118	TL	132/130 J	6.00	2000	4410	1900	4190	130	900	11.0	208	717	
	205/70R17.5	12	OH-120	TL	124/122 M	6.00	1600	3520	1500	3305	109	750	12.0	204	762	
		12	OH-322	TL	124/122 M	6.00	1600	3525	1500	3305	109	750	13.5	206	765	
	215/70R17.5	12	OH-117	TL	126/124 M	6.00	1700	3740	1600	3520	100	700	13.0	210	744	
	215/75R17.5	12	OH-109	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	10.0	210	768	
		12	OH-117	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	13.0	210	768	
		14	OH-311	TL	128/126 M	6.00	1800	3970	1700	3740	110	760	13.0	210	768	
		16	OH-109	TL	135/133 K	6.00	2180	4805	2060	4540	125	860	10.0	210	768	
		16	OH-117	TL	135/133 L	6.00	2180	4805	2060	4540	125	860	13.0	210	768	
		16	OH-117	TL	135/133 K	6.00	2180	4805	2060	4540	125	860	13.0	210	768	
16		OH-311	TL	135/133 K	6.00	2180	4850	2060	4540	125	860	13.0	210	768		
225/75R17.5	12	OH-117	TL	135/133 M	6.75	2180	4805	2060	4540	125	860	12.0	233	796		
	12	OH-311	TL	135/133 K	6.75	2180	4805	2060	4540	125	860	13.5	235	800		
225/80R17.5	14	OH-117	TL	123/122 L	6.75	1550	3415	1500	3305	102	700	12.0	224	804		



RADIAL TIRE



OH-120 OH-121 OH-122 OH-123 OH-127 OH-150 OH-151 OH-152 OH-153 OH-154

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
17.5"	225/80R17.5	14	OH-311	TL	123/122 L	6.75	1550	3415	1500	3305	102	700	16.0	228	814	
		14	OH-317	TL	123/122 J	6.75	1550	3415	1500	3305	102	700	18.0	226	816	
	235/75R17.5	14	OH-311	TL	132/130 M	6.75	2000	4410	1900	4190	112	775	13.5	235	800	
		16	OH-117	TL	135/133 M	6.75	2180	4805	2060	4540	125	860	12.0	233	796	
		16	OH-311	TL	135/133 K	6.75	2180	4805	2060	4540	125	860	13.5	235	800	
		18	OH-311	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	13.5	235	800	
	245/70R17.5	16	OH-117	TL	136/134 M	7.50	2240	4940	2120	4675	120	830	13.0	248	788	
		16	OH-322	TL	136/134 M	7.50	2240	4940	2120	4675	120	830	13.5	250	789	
		18	OH-117	TL	143/141 J (146/146 F)	7.50	2725	6010	2575	5680	125	860	13.0	248	788	
19.5"	225/70R19.5	14	OH-152	TL	128/126 L	6.75	1800	3970	1700	3750	110	760	13.5	220	814	
		14	OH-650	TL	128/126 L	6.75	1800	3970	1700	3750	110	760	15.0	220	817	
	245/70R19.5	14	OH-152	TL	133/131 L	7.50	2060	4540	1950	4300	110	760	13.5	243	839	
		16	OH-117	TL	136/134 M	7.50	2240	4940	2120	4675	120	830	-	-	-	
		16	OH-311	TL	136/134 L	7.50	2240	4940	2120	4675	120	830	15.0	250	845	
		16	OH-322	TL	136/134 M	7.50	2240	4940	2120	4675	120	830	14.5	248	845	
		18	OH-118	TL	141/140 J	7.50	2575	5675	2500	5510	123	850	12.5	249	840	
		18	OH-311	TL	144/142 J	7.50	2800	6175	2650	5840	130	900	15.0	250	845	
	265/70R19.5	16	OH-120	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	13.0	262	866	
		16	OH-204	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	15.0	260	870	
		16	OH-322	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	14.5	260	870	
		18	OH-118	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	14.0	262	869	
		18	OH-204	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	15.0	260	870	
		18	OH-204	TL	143/141 K	7.50	2725	6010	2575	5680	125	860	15.0	260	870	
	285/70R19.5	18	OH-303	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	16.0	260	873	
		16	OH-120	TL	146/144 M	8.25	3000	6010	2800	6175	130	900	13.0	279	894	
		16	OH-322	TL	146/144 M	8.25	3000	6010	2800	6175	130	900	14.5	282	892	
		18	OH-108	TL	150/148 J	8.25	3350	7390	3150	6940	130	900	14.0	281	896	
		18	OH-120	TL	148/145 M	9.00	3150	6940	2900	6395	123	850	14.0	297	925	
		18	OH-322	TL	148/145 M	9.00	3150	6940	2900	6395	123	850	14.5	305	924	
385/55R19.5	18	OH-111	TL	156 J	12.25	4000	8820	-	-	125	860	14.8	393	916		
435/50R19.5	-	OH-111	TL	160 J	14.00	4500	9920	-	-	130	900	12.5	436	927		
445/45R19.5	-	OH-111	TL	160 J	15.00	4500	9920	-	-	130	900	13.5	432	901		
20"	7.50R20	14	OH-211	TT	130/128 L	6.00	1900	4190	1800	3970	120	830	12.0	213	934	
	8.25R20	16	OH-303	TT	139/137 K	6.50	2430	5355	2300	5070	135	930	16.0	232	980	
	9.00R20	14	OH-121	TT	140/137 L	7.00	2500	5510	2300	5070	105	725	15.0	256	1022	
	10.00R20	16	OH-107	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	15.0	277	1053	
		16	OH-121	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	16.0	276	1055	
	16	OH-201	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	276	1058		

RADIAL TIRE



OH-155

OH-170

OH-201

OH-202

OH-203

OH-204

OH-205

OH-206

OH-208

OH-209

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
20"	10.00R20	16	OH-213	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	16.0	276	1055	
		16	OH-301	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	277	1060	
		16	OH-303	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	274	1058	
		18	OH-213	TT	149/145 K	7.50	3250	7160	2900	6395	135	930	6.0	276	1055	
		18	OH-121	TT	149/145 K	7.50	3250	7160	2900	6395	135	930	16.0	276	1055	
		18	OH-213	TT	149/145 K	7.50	3250	7160	2900	6395	135	930	16.0	276	1055	
		18	OH-403	TT	149/145 G	7.50	3250	7160	2900	6395	135	930	24.5	276	1072	
	11.00R20	16	OH-117	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	15.0	296	1083	
		16	OH-201	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.5	288	1089	
		16	OH-121	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.5	295	1089	
		16	OH-208	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	17.0	284	1089	
		16	OH-301	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.0	290	1087	
		16	OH-303	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	20.5	288	1093	
		18	OH-117	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	15.0	296	1083	
		18	OH-121	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	16.5	295	1089	
		18	OH-122	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	TBA	TBA	TBA	
		18	OH-302	TT	152/149 D	8.00	3550	7830	3250	7160	135	930	-	-	-	
		18	OH-201	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	16.5	288	1089	
		18	OH-208	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	17.0	284	1089	
		12.00R20	18	OH-213	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	18.0	295	1090
	18		OH-307	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	22.0	295	1099	
	18		OH-201	TT	154/150 K	8.50	3750	8270	3350	7390	125	860	16.0	310	1124	
	18		OH-210	TT	154/150 K	8.50	3750	8270	3350	7390	125	860	14.5	308	1120	
	18		OH-213	TT	154/150 K	8.50	3750	8270	3350	7390	125	860	18.5	310	1128	
	18		OH-403	TT	154/150 G	8.50	3750	8270	3350	7390	125	860	24.0	313	1137	
	20		OH-213	TT	156/153 K	8.50	4000	8820	3650	8050	130	900	18.5	310	1128	
	22.5"	10R22.5	14	OH-152	TL	141/139 L	7.50	2575	5675	2430	5355	115	790	13.5	256	1020
		11R22.5	14	OH-151	TL	144/142 L	8.25	2800	6175	2650	5840	105	720	10.5	280	1042
16			OH-107	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	280	1055	
16			OH-113	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	277	1053	
16			OH-117	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	280	1053	
16			OH-118	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	14.0	279	1059	
16			OH-121	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	17.0	278	1054	
16			OH-123	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	TBA	TBA	TBA	
16			OH-127	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	TBA	TBA	TBA	
16	OH-150	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	14.0	277	1052			



RADIAL TIRE



OH-210

OH-211

OH-213

OH-301

OH-302

OH-303

OH-305

OH-306

OH-307

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
22.5"	11R22.5	16	OH-153	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	15.0	276	1053	
		16	OH-154	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	14.0	279	1052	
		16	OH-201	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	16.0	280	1055	
		16	OH-205	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	16.5	280	1051	
		16	OH-301	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	19.5	280	1061	
		16	OH-302	TL	148/145 F	8.25	3150	6940	2900	6395	125	860	23.0	280	1067	
		16	OH-303	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	18.0	280	1058	
		16	OH-312	TL	148/145 K	8.25	3150	6940	2900	6395	125	860	22.0	283	1067	
		16	OH-320	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	18.0	283	1058	
		16	OH-350	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	20.5	277	1064	
		16	OH-351	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	20.5	273	1064	
		16	OH-403	TL	146/143 G	8.25	3000	6610	2725	6005	120	830	24.5	280	1071	
	12R22.5	16	OH-107	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	16.0	300	1088	
		16	OH-121	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	16.5	306	1090	
		16	OH-301	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	22.0	309	1100	
		16	OH-127	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	TBA	TBA	TBA	
		18	OH-107	TL	152/149 K	9.00	3550	7830	3250	7160	135	930	16.0	300	1088	
		18	OH-121	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	16.5	306	1090	
		18	OH-122	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	TBA	TBA	TBA	
		18	OH-127	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	TBA	TBA	TBA	
		18	OH-209	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	16.5	298	1082	
		18	OH-213	TL	152/149 K	9.00	3550	7830	3250	7160	135	930	18.0	306	1092	
		18	OH-301	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	22.0	309	1100	
		18	OH-312	TL	152/149 K	9.00	3550	7830	3250	7160	125	860	23.0	298	1092	
13R22.5	18	OH-403	TL	154/150 G	9.00	3750	8270	3350	7390	125	860	24.0	298	1105		
	18	OH-210	TL	156/150 K	9.75	4000	8820	3350	7390	125	860	18.5	319	1120		
	18	OH-312+	TL	156/150 K	9.75	4000	8820	3350	7390	125	860	22.5	328	1130		
255/70R22.5	18	OH-403	TL	156/150 G	9.75	4000	8820	3350	7390	125	860	25.5	319	1140		
	16	OH-107	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	13.5	255	935		
	16	OH-152	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	11.0	254	931		
275/70R22.5	16	OH-350	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	20.0	253	945		
	16	OH-107	TL	148/145 M	8.25	3150	6940	2900	6395	130	900	15.0	276	963		
	16	OH-320	TL	148/145 M	8.25	3150	6940	2900	6395	130	900	18.0	279	969		
275/80R22.5	16	OH-501	TL	150/148 J (152/148 E)	8.25	3350	7390	3150	6940	130	900	17.0	282	967		
	18	OH-107	TL	152/148 J	8.25	3550	7830	3150	6940	130	900	15.0	276	963		
275/80R22.5	16	OH-121	TL	149/146 M	8.25	3250	7160	3000	6610	125	860	16.5	271	1021		
	16	OH-302	TL	149/146 G	8.25	3250	7160	3000	6610	125	860	20.0	271	1029		
295/60R22.5	16	OH-107	TL	150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	12.5	287	925		

RADIAL TIRE



OH-311

OH-312

OH-312+

OH-314

OH-317

OH-319

OH-320

OH-322

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
22.5"	295/60R22.5	16	OH-311	TL	150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	18.0	287	937	
		16	OH-320	TL	150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	17.0	288	935	
	295/75R22.5	14	OH-150	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	14.0	298	1014	
		14	OH-151	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	10.5	293	1016	
		14	OH-153	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	15.0	295	1024	
		14	OH-154	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	14.5	296	1023	
		14	OH-350	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	20.5	293	1036	
		14	OH-351	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	20.5	293	1035	
	295/80R22.5	16	OH-301	TL	148/145 M	9.00	3150	6940	2900	6395	125	860	22.0	298	1038	
		16	OH-107	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	15.0	300	1050	
		16	OH-121	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	300	1055	
		16	OH-201	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	302	1052	
		16	OH-206	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	300	1055	
		16	OH-301	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	22.5	300	1066	
		16	OH-302	TL	152/148 F	9.00	3550	7830	3150	6940	125	860	23.5	300	1066	
		16	OH-312	TL	152/148 K	9.00	3550	7830	3150	6940	125	860	22.0	300	1064	
		16	OH-320	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	20.0	303	1060	
		18	OH-107	TL	154/150 M	9.00	3750	8270	3350	7390	125	860	15.0	300	1050	
	315/60R22.5	16	OH-107	TL	154/148 L	9.75	3750	8270	3150	6940	130	900	12.5	301	948	
		16	OH-311	TL	154/148 L	9.75	3750	8270	3150	6940	130	900	18.0	305	960	
		16	OH-320	TL	154/148 L	9.75	3750	8270	3150	6940	130	900	17.0	313	960	
		16	OH-107	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	15.0	322	1014	
		16	OH-301	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	22.0	322	1030	
		16	OH-319	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	16.5	320	1019	
	315/70R22.5	16	OH-320	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	21.5	322	1030	
		18	OH-107	TL	156/150 L	9.00	4000	8820	3350	7390	130	900	15.0	322	1014	
		20	OH-107	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	16.0	314	1086	
		20	OH-121	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	17.0	315	1084	
		20	OH-201	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	15.5	314	1084	
		20	OH-209	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	15.5	318	1082	
		20	OH-301	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	22.5	314	1095	
		20	OH-301	TL	160/157 L	9.00	4535	10000	4125	9090	130	900	22.5	314	1095	
315/80R22.5	20	OH-312+	TL	156/150 K	9.00	4000	8820	3350	7390	125	860	22.5	314	1095		
	20	OH-319	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	16.5	316	1084		
	20	OH-320	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	21.5	315	1095		
	20	OH-320	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	21.5	315	1095		



RADIAL TIRE



OH-350 OH-351 OH-401 OH-402 OH-403 OH-404 OH-501 OH-650

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH		MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		INFLATED DIMENSION (mm)		
						(Inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	
22.5"	315/80R22.5	20	OH-402	TL	156/150 K	9.00	4000	8820	3350	7390	125	860	21.5	314	1095	
		22	OH-107	TL	158/150 L	9.00	4250	9370	3350	7390	130	900	16.0	314	1086	
		22	OH-121	TL	158/150 L	9.00	4250	9370	3350	7390	130	900	17.0	315	1084	
		22	OH-201	TL	158/150 L	9.00	4250	9370	3350	7390	130	900	15.5	314	1084	
	355/50R22.5	18	OH-108	TL	156 K	11.75	4000	8820	-	-	130	900	13.5	260	933	
	385/55R22.5	20	OH-108	TL	160 K	12.25	4500	9920	-	-	130	900	13.0	386	996	
		20	OH-119	TL	160 K (158L)	12.25	4500	9920	-	-	130	900	15.0	388	998	
	385/65R22.5	20	OH-102	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	15.0	380	1074	
		20	OH-108	TL	160 K	11.75	4500	9920	-	-	130	900	14.0	388	1078	
		20	OH-119	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	15.0	387	1070	
		20	OH-203	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	16.5	380	1074	
		-	OH-108	TL	164 K	11.75	5000	11025	-	-	130	900	14.0	388	1078	
		22	OH-119	TL	164 K Extra Load	11.75	5000	11000	-	-	130	900	15.0	387	1070	
	425/65R22.5	20	OH-306	TL	165 K	13.00	5150	11400	-	-	120	830	18.0	426	1130	
	445/65R22.5	20	OH-306	TL	169 K	13.00	5800	12800	-	-	130	900	16.5	439	1158	
455/40R22.5	-	OH-111	TL	160 J	15.00	4500	9920	-	-	130	900	13.5	440	935		
24"	12.00R24	20	OH-202	TL	160/156 K	8.50	4500	9920	4000	8820	125	860	14.0	310	1214	
	325/95R24 (12.00R24)	22	OH-201	TL	162/160 K	9.00	4750	10500	4500	9920	125	860	19.0	312	1229	
		22	OH-401	TL	162/160 F	9.00	4750	10500	4500	9920	125	860	28.0	312	1235	
		22 16	OH-404	TL	162/160 F	9.00	4750	10500	4500	9920	125	860	31.0	313	1230	
24.5"	11R24.5	16	OH-150	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	14.5	280	1104	
		16	OH-153	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	15.0	287	1102	
		16	OH-154	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	14.5	291	1101	
		16	OH-201	TL	149/146 K	8.25	3250	7160	3000	6610	120	830	19.0	289	1113	
		16	OH-350	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	20.0	286	1115	
		16	OH-351	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	20.5	284	1115	
		16	OH-403	TL	149/146 G	8.25	3250	7160	3000	6610	120	830	24.5	281	1123	
	285/75R24.5	14	OH-150	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	14.5	282	1053	
		14	OH-153	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	15.0	281	1062	
		14	OH-155	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	14.0	288	1051	
14	OH-350	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	20.0	285	1051			

OTANI RADIAL CO., LTD.

96 MU 3 RIMKLONGBANRAI ROAD,
BANGKAEW, NAKHON CHAI SI,
NAKHON PATHOM 73120 THAILAND

WEBSITE :

E-MAIL :

OFFICIAL LINE ACCOUNT :

FACEBOOK FANPAGE :

WWW.OTANITIRE.COM

SALES@OTANITIRE.COM

@OTANITIRE

OTANI TIRE

