

Made in Thailand



OTANI[®]
DRIVING CONFIDENCE

CATALOG 2026

AGRICULTURAL TIRE



OTANI TIRE CO., LTD.

55 MU 7 PHETKASEM ROAD KM.37,
KLONGMAI, SAM PHRAN,
NAKHON PATHOM 73110 THAILAND
Tel. : +66 3432 5000

WEBSITE :

E-MAIL :

OFFICIAL LINE ACCOUNT :

FACEBOOK FANPAGE :

WWW.OTANITIRE.COM

SALES@OTANITIRE.COM

@OTANITIRE

OTANI TIRE



WWW.OTANITIRE.COM

AGRICULTURAL TIRE



F-30



F-32



F-33



F-34



F-35



F-36



F-37



F-38



F-39



F-41



F-80



F-85



G-45



K-81



K-82



T-22



T-25

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH	
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)	
12"	10.0/80-12	6	K-82	-	TT	W7	30	33	230	1060	266	703	10	
14"	6-14	4	F-33	R1 / G1	TT	5AJ	30	28	195	300	162	655	28	
	7-14	4	F-33	R1 / G1	TT	5AJ	30	25	170	355	178	687	28	
15"	6.50-14	8	F-33	R1	TT	4.50E	30	46	315	710	183	699	19	
	4.00-15	6	T-22	II	TT	3.00D	30	64	440	425	114	610	10	
16"	6.00-16	6	T-22	II	TT	4.00E	30	48	330	560	177	740	15	
		8	T-22	II	TT	4.00E	30	65	450	670	180	750	15	
	7-16	4	F-33	R1 / G1	TT	5AJ	30	24	165	387	183	740	26	
	7.50-16	8	F-30	-	TT	5.50F	40	40	275	875	207	893	57	
		8	F-33	R1	TT	5.50F	40	54	370	875	220	816	20	
		8	F-34	R1	TT	5.50F	40	54	370	875	208	814	25	
		6	T-22	II	TT	5.50F	40	44	305	670	210	814	20	
		8	T-22	II	TT	5.50F	40	54	370	875	210	814	20	
		8	T-25	II	TT	5.50F	40	54	370	875	208	805	17	
	8-16	4	F-33	R1 / G1	TT	W6	30	18	125	487	211	796	31	
		6	F-33	R1 / G1	TT/TL	W6	30	28	195	615	211	798	31	
	9.5-16	6	F-33	R1 / G1	TT	W8	30	32	220	730	245	850	30	
		6	F-80	R2	TT	W8	30	32	220	730	260	845	43	
	9.00-16	8	F-33	R1	TT	W8	40	45	310	1090	234	843	20	
		10	T-22	II	TT	W8	40	52	360	1500	232	848	17	
	10.00-16	8	T-22	II	TL	W8	40	41	285	1215	272	898	19	
	11.00-16	8	T-22	II	TL	W10	40	36	250	1320	305	947	22	
	11L-16LS	12	K-81	I3 / F3	TL	8LB	30	52	360	1250	263	832	12	
	18"	7.50-18	8	F-33	R1	TT	5.50F	40	54	370	950	210	860	20
			8	T-22	II	TT	5.50F	40	54	370	950	220	864	20
8-18		6	F-33	R1 / G1	TT/TL	W6	30	28	195	670	222	840	31	
		6	F-35	R1 / G1	TT	W6	30	28	195	670	222	845	34	
		8	F-33	R1	TT	W7	30	42.06	290	850	211	839	28	
		8	F-35	R1 / G1	TT	W6	30	42	290	850	222	845	34	
		10	F-33	R1 / G1	TT	W6	30	18	125	515	221	840	31	
10	F-35	-	TT	W7	30	42.06	290	850	211	839	31			
13.0/65-18	16	K-82	I3 / F3	TL	11.00	40	95	655	2800	330	898	12		
20"	8.3-20	6	F-35	R1	TT	W7	30	35	240	710	208	890	30	
	9.5-20	6	F-36	R1	TT	W7	40	32	220	850	240	945	43	
		8	F-36	R1	TT	W7	40	41	285	975	244	948	43	
11.2-20	8	F-35	R1	TT	W9	40	36	250	1150	280	1010	30		
22"	9.5-22	6	F-36	R1	TT	W8	40	31	215	900	240	1010	40	
24"	8.3-24	6	F-35	R1	TT	W7	40	34	235	800	208	996	30	
		6	F-35	R1	TT	W8	40	30	205	850	241	1048	30	
	9.5-24	6	F-37	R1	TT	W8	40	30	205	850	241	1085	57	
		6	F-37	R1	TT	W8	40	30	205	850	241	1085	57	
	11.2-24	6	F-37	R1	TT	W10	40	26	180	1060	284	1103	57	
		8	F-39	R1	TT	W10	40	35	240	1250	284	1110	42	
	12.4-24	8	F-33	R1	TT	W11	40	32	220	1285	286	1160	28	
		10	F-33	R1	TT	W11	40	36	250	1550	288	1160	28	
		12	F-33	R1	TT	W11	40	48	330	1600	288	1161	28	
		4	F-37	R1	TT	W11	40	16	110	850	318	1160	57	
		6	F-37	R1	TT	W11	40	25	170	1215	320	1165	57	
		8	F-37	R1	TT	W11	40	32	220	1285	322	1170	57	
	13.6-24	6	F-37	R2	TT	W12	40	22	150	1215	345	1210	57	
		8	F-37	R2	TT	W12	40	28	195	1400	348	1215	57	
		8	F-39	R1	TT	W12	40	28	195	1400	346	1212	42	
		12	F-39	R1	TT	W12	40	36	250	1650	348	1215	42	

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)
24"	14.9-24	8	F-32	R1	TT/TL	W13	40	26	180	1800	389	1240	30
		12	F-32	R1	TT/TL	W13	40	38	260	2180	395	1245	30
		6	F-33	R1	TT/TL	W13	40	20	140	1550	378	1280	35
		8	F-33	R1	TT	W13	40	26	180	1800	385	1285	35
		12	F-33	R1	TT/TL	W13	40	38	260	2180	386	1286	35
		8	F-37	R2	TT	W13	40	26	180	1800	378	1285	60
	15.5/80-24	8	G-45	R4	TT/TL	W13	40	30	205	2300	397	1271	27
		10	G-45	R4	TT/TL	W13	40	36	250	2800	405	1272	27
	16.9-24	12	F-39	R1	TL	W12	40	58	400	4875	390	1275	38
		8	G-45	R4	TT/TL	W15L	40	28	195	2650	440	1360	27
	17.5L-24	10	G-45	R4	TT/TL	W15L	40	32	220	2900	445	1362	27
		12	G-45	R4	TT/TL	W15L	40	38	260	3250	450	1363	27
	18.4-24	10	G-45	R4	TT/TL	DW15L	40	32	220	2800	456	1310	27
		12	G-45	R4	TT/TL	DW15L	40	36	250	2995	460	1321	27
	19.5L-24	10	G-45	R4	TT/TL	W16L	40	28	195	3350	472	1412	28
		12	G-45	R4	TT/TL	W16L	40	36	250	3750	480	1414	28
21L-24	10	G-45	R4	TT/TL	DW16L	40	30	205	3000	495	1312	27	
	12	G-45	R4	TT/TL	DW16LL	40	34	235	3450	496	1314	27	
14	G-45	R4	TT/TL	DW16L	40	40	275	3750	498	1315	27		
12	G-45	R4	TT/TL	DW18L	40	34	235	3447	558	1410	28		
25"	23.5-25	20	F-41	E2/L2	TL	19.5/2.50	40	34	235	10900	630	1638	54
26"	13.6-26	6	F-35	R1	TT/TL	W12	40	22	150	1250	345	1276	47
		8	F-35	R1	TT	W12	40	26	180	1600	348	1280	47
		6	F-37	R2	TT	W12	40	22	150	1250	345	1260	57
	8	F-37	R2	TT	W12	40	26	180	1600	345	1261	57	
23.1-26	16	F-38	R1	TT/TL	DW20B	40	32	220	4375	615	1605	42	
28L-26	26	F-38	LS-2	TL	W25	30	58.02	400	9000	744	1659	51	
28"	12.4-28	6	F-37	R1	TT	W11	40	25	170	1285	315	1260	53
		8	F-33	R1	TT	W11	40	26	180	1500	305	1257	28
		10	F-33	R1	TT	W11	40	32	220	1650	306	1259	28
		12	F-33	R1	TT	W11	40	34	235	1750	307	1260	28
		9	F-39	R1	TT	W11	40	26	180	1500	320	1277	40
	13.6-28	6	F-37	R2	TT	W12	40	23	160	1450	345	1310	57
		8	F-37	R2	TT	W12	40	29	200	1650	348	1313	57
	14.9-28	6	F-35	R1	TT	W13	40	20	140	1650	372	1361	40
		8	F-35	R1	TT	W13	40	26	180	1900	375	1363	40
		12	F-35	R1	TT	W13	40	38	260	2300	378	1365	40
		6	F-36	R2	TT	W13	40	20	140	1650	378	1385	55
		8	F-36	R2	TT	W13	40	26	180	1900	380	1388	55
		8	F-33	R1	TT	W15L	40	25	170	2180	430	1430	40
	13.6-28	10	F-33	R1	TT	W15L	40	29	200	2430	435	1435	40
		12	F-80	R2	TT	W15L	40	35	240	2725	439	1435	57
		8	G-45	R4	TT/TL	W15L	40	28	195	2800	429	1400	27
10		G-45	R4	TT/TL	W15L	40	32	220	3075	430	1405	27	
12		G-45	R4	TT/TL	W15L	40	38	260	3450	432	1410	27	
14.9-30		8	F-35	R1	TT	W13	30	26	180	1950	395	1436	48
16.9-30	8	F-33	R1	TT	W15L	40	25	170	2300	436	1483	40	
	10	F-33	R1	TT	W15L	40	28	195	2430	437	1486	40	
	12	F-33</											

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TRA CODE	TYPE	STANDARD RIM WIDTH	MAXIMUM SPEED	RELATIVE PRESSURE		MAXIMUM LOAD	INFLATED DIMENSION (mm)		TREAD DEPTH
						(Inch)	(km/h)	(psi)	(kPa)	(kg)	SECTION WIDTH	OVERALL DIAMETER	(mm)
30"	18.4-30	12	F-33	R1	TT	W16L	40	33	230	3250	483	1548	46
		8	F-39	R1	TT	W16L	40	20	140	2430	480	1544	53
		10	F-39	R1	TT	W16L	40	26	180	2900	483	1546	53
		12	F-39	R1	TT	W16L	40	33	230	3250	487	1548	53
		14	F-39	R1	TT	W16L	40	38	260	3450	488	1550	53
		12	F-80	R2	TT	W6L	40	33	230	3250	491	1595	77
32"	9.5-32	6	F-35	R1	TT	W8	40	30.46	210	950	246	1268	27
		6	F-36	R1	TT	W12	40	31	210	1060	240	1255	30
	12.4-32	8	F-35	R1	TT	W8	40	46.41	320	1250	246	1268	27
		8	F-35	R1	TT	W12	40	33	230	1600	315	1265	40
34"	16.9-34	8	F-39	R1	TT	W15L	40	25	170	2430	463	1640	53
		10	F-39	R1	TT	W15L	40	29	200	2650	475	1644	53
	18.4-34	8	F-33	R1	TT	W16L	40	20	140	2650	480	1635	46
		10	F-33	R1	TT	W16L	40	26	180	3000	480	1637	46
		6	F-36	R2	TT	W16L	40	26	180	3000	480	1650	49
		10	F-39	R1	TT	W16L	40	26	180	3000	483	1659	53
		6	F-85	R2	TT	W16L	40	16	110	2000	491	1722	81
38"	13.6-38	8	F-38	R1	TT	W12	40	29	200	1950	345	1555	40
	15.5-38	8	F-38	R1	TT	W14	40	26	180	1850	401	1555	34
		10	F-38	R1	TT	W14	40	32	220	2180	403	1560	34
	16.9-38	8	F-38	R1	TT	W15L	40	25	170	2575	430	1685	40
		10	F-38	R1	TT	W15L	40	29	200	2725	433	1690	40
	18.4-38	10	F-39	R1	TT	W16L	40	26	180	2900	487	1795	53
8		F-85	R2	TT	W16L	40	20	140	2725	485	1798	81	
	20-8.38	8	F-85	R2	TT	W18L	40	19	130	3150	535	1904	85

• Tire construction and material specifications are subject to change without notice nor obligation.

AGRICULTURAL RADIAL TIRE



RIM DIAMETER	TIRE SIZE	LI/SS	PATTERN	TRA CODE	TYPE	MAX SPEED	RIM WIDTH		RELATIVE PRESSURE			LOAD LIMITS	INFLATED DIMENSION (mm)	
							REC. RIM	ALT. RIM	psi	kPa	kg/cm ²	kg	SECTION WIDTH	OVERALL DIAMETER
							km/h	(Inch)						
24"	320/85R24 (12.4-24)	119D/122A8	A-10	R-1W	TT/TL	65	10	9-11	23.21	160	1.63	1360/1500	320	1144
	340/85R24 (13.6-24)	122D/125A8	A-10	R-1W	TT/TL	65	11	10-12	23.21	160	1.63	1500/1650	348	1181
	380/85R24 (14.9-24)	128D/131A8	A-10	R-1W	TT/TL	65	12	11-13	23.21	160	1.63	1800/1950	381	1241
	420/70R24 (16.9-24)	134D/137A8	A-20	R-1W	TL	65	13	12-14	29.01	200	2.04	2120/2300	427	1259
	460/70R24 (18.4-24)	156D/159A8	A-20	R-1W	TL	65	14	13-15	23.21	160	1.63	4000/4375	456	1280
28"	340/85R28 (13.6-28)	124D/127A8	A-10	R-1W	TL	65	11	10-12	23.21	160	1.63	1600/1750	350	1284
	380/85R28 (14.9-28)	130D/133A8	A-10	R-1W	TL	65	12	11-13	23.21	160	1.63	1900/2060	381	1350
	420/85R28 (16.9-28)	136D/139A8	A-10	R-1W	TL	65	13	12-14	23.21	160	1.63	2240/2430	429	1429
	540/65R28 (16.9-28)	142D/145A8	A-10	R-1W	TL	65	18	17-19	34.81	240	2.45	2650/2900	551	1416
	420/70R28 (16.9-28)	133D/136A8	A-20	R-1W	TL	65	13	12-14	23.21	160	1.63	2060/2240	419	1353
	480/70R28 (16.9-28)	140D/143A8	A-20	R-1W	TL	65	15	14-16	23.21	160	1.63	2500/2725	480	1427
	600/65R28 (16.9-30)	154D/157A8	A-10	R-1W	TL	65	18	17-19	35	240	2.04	3750/4125	592	1465
30"	420/85R30 (16.9-30)	137D/140A8	A-10	R-1W	TT/TL	65	13	12-14	23.21	160	1.63	2300/2500	439	1464
	460/85R30 (18.4-30)	142D/145A8	A-10	R-1W	TT/TL	65	14	13-15	23.21	160	1.63	2650/2900	467	1571
	480/70R30 (16.9-30)	141D/144A8	A-20	R-1W	TL	65	15	14-16	23.21	160	1.63	2575/2800	480	1495
	540/65R30 (16.9-30)	150D/153A8	A-10	R-1W	TL	65	18	17-19	35	240	2.04	3350/3650	551	1445
34"	460/85R34 (18.4-34)	144D/147A8	A-10	R-1W	TT/TL	65	14	13-15	23.21	160	1.63	2800/3075	466	1651
	420/85R34 (16.9-34)	142D/145A8	A-20	R-1W	TL	65	13	12-14	23.21	160	1.63	2650/2900	420	1555
	480/70R34 (16.9-34)	149D/152B	A-20	R-1W	TL	65	15	14-16	34.81	240	2.45	3250/3550	481	1558
38"	460/85R38 (18.4-38)	146D/149A8	A-10	R-1W	TT/TL	65	14	13-15	23.21	160	1.63	3000/3250	458	1753
	420/85R38 (16.9-38)	141D/144A8	A-10	R-1W	TL	65	13	12-14	23.21	160	1.63	2575/2800	420	1679
	480/70R38 (16.9-38)	145D/148A8	A-20	R-1W	TL	65	15	14-16	23.21	160	1.63	2900/3150	480	1658

• Tire construction and material specifications are subject to change without notice nor obligation.